


WORLD INTELLECTUAL PROPERTY ORGANIZATION



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:		(11) International Publication Number: WO 00/32268
A61N 1/375, H01R 4/48 // 4/26	A1	(43) International Publication Date: 8 June 2000 (08.06.00)
(21) International Application Number: PCT/SE99/02083 (22) International Filing Date: 15 November 1999 (15.11.99)		DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT,
(30) Priority Data: 9804138-7 30 November 1998 (30.11.5	98) S	Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.
(71) Applicant (for all designated States except US): PACI AB [SE/SE]; S-175 84 Järfälla (SE).	SETTE	
(72) Inventor; and (75) Inventor/Applicant (for US only): HILL, Rolf Gösvägen 8, S–175 55 Järfälla (SE).	[SE/SI	0);
(74) Common Representative: PACESETTER AB; Pater ment, S-175 84 Järfälla (SE).	nt Depa	п-

(54) Title: DEVICE IN CONNECTION WITH PACERS



(57) Abstract

The invention relates to a locking device (1) for a female connector part for cooperation with an elongate, male connector part (30), freale female connector part comprises a longitudinal space for said locking device. Said locking device comprises one or several tongues (19, 19) being swingable between two positions, a first position in which the tips of the tongues (19, 19) can emale clongate connector part (30) and a second position in which the tips of the tongues (19, 19) will not engage the male clongate connector part (30) and a second position in which the tips of the tongues (19, 19) will not engage the male clongate connector part (30) and a second position in which the tips of the tongues (19, 19) will not engage the male clongate connector part (30). Said tongues are biased towards said first position by means of a spring force. A pivot (9) is associated with each tongue and each tongue has a first part engaging said connector means (30) and being located on one side of said pivot and a second part being located on the other side of said pivot. Longitudinally acting means (4) are provided to act on said second part of said tongues (19, 19) for actuating said tongues from said first position against said bias to said second position.